



## Red-Light Reflex Light Barrier with Gloss Suppression

### Type JP197



Scale 1: 2.5



0 - 20m

Red-Light Reflex Light Barrier with Gloss Suppression


JP197

#### Technical characteristics of minimum type:

Housing	Al-Cast
Weight	approx. 350g
Protection mode	IP65
Connection	6+1 pin plug stH7
Supply	20...230VUC/~2VA
Output	Relais 240VAC/5A, 120W/1200VA, 1xCh.
Signal mode	brightswitching
Transmitter light JP195:	LED 650nm (visible)
Gloss suppression	polarization
Steady light resistance	>80kLx
Interference suppress.	Force synchronization
Light beam diameter	approx. 85mm/6m
Access time	<12ms/Switch transition
Switching rate	~10/s
Switch indicator	LED green
Ambient temperatur	-30...+65°C (90°C*)

\*Exceeding the temperature for a short time does not usually impair functioning

#### Connection diagramm:



Order no.:

1043


#### Features:

Signal mode darkswitching

#### Accessories:

- Reflectors
- Diaphragm
- Adjustment flange JF19H(1)
- Elbow tube adjustment JR19(2&3)
- Anti heat shield & anti dust tube (K)JT19

#### Adjustment assemblies:



#### Diaphragm:

